



EQUIPMENT SOLUTIONS  
BY GO INDUSTRY



GREEN SPACE AND GARDEN



HANDLING AND PUBLIC WORKS



AGRICULTURAL EQUIPMENT

CHARGEUR PLUS  
3 rue Jacques de Vaucanson  
17180 Périgny



contact@chargeurplus.fr  
+33 (0)5 46 56 18 88  
www.chargeurplus.com

# GREEN SPACE AND GARDEN MINI EXCAVATORS WITH PETROL ENGINE



The Chargeur Plus mini excavators can:

- Dig with the 20 cm and 30 cm digging buckets,
- Dredge, load and level out with the 60 cm bucket,
- Load and transport with the loading bucket,
- Plow and remove roots with the ripper 1 tooth and 4 teeth.

- Drill with the 100, 150 and 200 diameter of auger drilling attachments,
- Move logs and other materials with the 800 kg grapple,
- Break up concrete with a hydraulic hammer,
- Split logs with a cone splitter.

It is fully mechanical and hydraulic, there is no electronic installed.

	MP-72-800-S	MPT-72-800-S	MPT-72-1200-S	MPT-72-1200-P	MPT-72-1200-P+	MP-82-1500-S	MPT-82-1500-S	MPT-82-1500-P	MPT-82-1500-P+
<b>Kind of use</b>	Occasional	Occasional	Occasional	Regular	Regular	Occasional	Occasional	Regular	Regular
<b>Weight in standard range</b>	385 kg	410 kg	420 kg	425 kg	435 kg	750 kg	775 kg	780 kg	790 kg
<b>Engine</b>	6,5 HP Excalibur - 4,4 kW	6,5 HP Excalibur - 4,4 kW	9 HP Excalibur - 6,6 kW	9,5 HP Kohler - 7kw	14 HP Kohler - 10,3kw	9 HP Excalibur - 6,6 kW	9 HP Excalibur - 6,6 kW	9,5 HP Kohler - 7kw	14 HP Kohler - 10,3kw
<b>Track width</b>	720 mm	720 mm	720 mm	720 mm	720 mm	820 mm	820 mm	820 mm	820 mm
<b>Digging capacity</b>	800 kg	800 kg	1200 kg	1200 kg	1200 kg	1500 kg	1500 kg	1500 kg	1500 kg
<b>Maximum digging depth</b>	950 mm	950 mm	950 mm	950 mm	950 mm	1700 mm	1700 mm	1700 mm	1700 mm
<b>Excavating height</b>	1600 mm	1600 mm	1600 mm	1600 mm	1600 mm	1700 mm	1700 mm	1700 mm	1700 mm
<b>Boom swing</b>	Hydraulic -55°/+55°	Manual -55°/+55°	Manual -55°/+55°	Hydraulic -55°/+55°	Hydraulic -55°/+55°	Hydraulic -55°/+55°	Manual -55°/+55°	Hydraulic -55°/+55°	Hydraulic -55°/+55°
<b>Turret 360°</b>	No	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes
<b>Handles position</b>	In front	In front	In front	On the sides	On the sides	On the sides	On the sides	On the sides	On the sides
<b>Traction motors</b>	Standard 200 cc	Standard 200 cc	Standard 200 cc	Professional 200 cc	Professional 200 cc	Standard 250 cc	Standard 250 cc	Professional 250 cc	Professional 250 cc
<b>Distributors</b>	Non-proportional	Non-proportional	Non-proportional	Proportional	Proportional	Non-proportional	Non-proportional	Proportional	Proportional
<b>Hydraulic pump flow</b>	Simple 13,3L/mn	Simple 13,3L/mn	Simple 13,3L/mn	Double 2x11,5L/mn	Double 2x17,25L/mn	Double 2x11,5L/mn	Double 2x11,5L/mn	Double 2x11,5L/mn	Double 2x17,25L/mn
<b>Included accessories</b>	Bucket 30 cm, electrical ignition	Bucket 30 cm, electrical ignition	Bucket 30 cm, electrical ignition	Bucket 30 cm, electrical ignition	Bucket 30 cm, electrical ignition, quick hitch, gripper fingers above the bucket, additional hydraulic line, oil cooler	Bucket 30 cm, electrical ignition	Bucket 30 cm, electrical ignition	Bucket 30 cm, electrical ignition	Bucket 30 cm, electrical ignition, quick hitch, gripper fingers above the bucket, additional hydraulic line, oil cooler
<b>Prices</b>	<b>4831 €</b> excl. taxes	<b>5906 €</b> excl. taxes	<b>6722 €</b> excl. taxes	<b>7822 €</b> excl. taxes	<b>8966 €</b> excl. taxes	<b>6190 €</b> excl. taxes	<b>7601 €</b> excl. taxes	<b>8690 €</b> excl. taxes	<b>9986 €</b> excl. taxes

## OPTIONS

- Quick hitch
- Telescopic arm
- Hydraulic hammer
- Ripper 1 tooth
- Ripper 4-Teeth
- Gripper fingers above the bucket
- Bucket 20, 30, 60 cm (dredging)
- Trapezium bucket, loading bucket
- 800 kgs grapple
- Additional hydraulic line
- Push Pull coupling
- Counterweight support (without weights)
- Counterweight (max 7 units - 19 kg each)
- Oil cooler
- Complete auger drilling 100, 150 or 200 mm
- Log splitter

# GREEN SPACE AND GARDEN MINI EXCAVATORS WITH PLUG IN ELECTRIC



The mini excavators Chargeur Plus with pivoting joint are available in plug in electric version, single-phase or tri-phase.

Variator in option.

Plug in electric mini excavator in single-phase:

- MMT-72-800-S
- MMT-72-1200-P
- MMT-82-1500-S

Plug in electric mini excavator in three-phase:

- MTT-72-1200-P
- MTT-82-1500-S
- MTT-82-1500-P

	MMT-72-800-S	MMT-72-1200-P	MTT-72-1200-P	MMT-82-1500-S	MTT-82-1500-S	MTT-82-1500-P
<b>Weight in standard range</b>	385 kg	425 kg	425 kg	750 kg	775 kg	780 kg
<b>Engine</b>	Single-phase 3kW	Single-phase 3kW	Three-phase 5,5kW	Single-phase 3kW	Three-phase 5,5kW	Three-phase 5,5kW
<b>Voltage</b>	240 V	240 V	380 V	240 V	380 V	380 V
<b>Track width</b>	720 mm	720 mm	720 mm	820 mm	820 mm	820 mm
<b>Digging capacity</b>	800 kg	1200 kg	1200 kg	1500 kg	1500 kg	1500 kg
<b>Maximum digging depth</b>	950 mm	950 mm	950 mm	1700 mm	1700 mm	1700 mm
<b>Excavating height</b>	1600 mm	1600 mm	1600 mm	1700 mm	1700 mm	1700 mm
<b>Boom swing</b>	Manual -55°/+55°	Hydraulic -55°/+55°	Hydraulic -55°/+55°	Manual -55°/+55°	Hydraulic -55°/+55°	Hydraulic -55°/+55°
<b>Turret 360°</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>Handles position</b>	In front	On the sides	On the sides	On the sides	On the sides	On the sides
<b>Traction motor</b>	Standard 200 cc	Professional 200 cc	Professional 200 cc	Standard 250 cc	Standard 250 cc	Professional 250 cc
<b>Distributors</b>	Non- proportional	Proportional	Proportional	Non- proportional	Non- proportional	Proportional
<b>Hydraulic pump flow</b>	Simple 10,4L/mn	Double 2x8,9L/mn	Double 2x13,9L/mn	Double 2x8,9L/mn	Double 2x13,9L/mn	Double 2x13,9L/mn
<b>Included accessories</b>	Bucket 30 cm, electrical ignition	Bucket 30 cm, electrical ignition	Bucket 30 cm, electrical ignition	Bucket 30 cm, electrical ignition	Bucket 30 cm, electrical ignition	Bucket 30 cm, electrical ignition
<b>Prices</b>	<b>6780 € excl. taxes</b>	<b>8690 € excl. taxes</b>	<b>8890 € excl. taxes</b>	<b>8370 € excl. taxes</b>	<b>8590 € excl. taxes</b>	<b>9920 € excl. taxes</b>

## OPTIONS

- Quick hitch
- Telescopic arm
- Hydraulic hammer
- Ripper 1 tooth
- Ripper 4-Teeth
- Gripper fingers above the bucket
- Bucket 20, 30, 60 cm (dredging)
- Trapezium bucket, loading bucket
- 800 kgs grapple
- Additional hydraulic line
- Push Pull coupling
- Counterweight support (without weights)
- Counterweight (max 7 units - 19 kg each)
- Oil cooler
- Complete auger drilling 100, 150 or 200 mm
- Log splitter

# HANDLING AND PUBLIC WORKS TRACKED DUMPERS



The tracked dumpers can move 300 kg to 600 kg and empty the contents with its hydraulic tipper.

Their 200 L to 320 L buckets can transport concrete, sand, earth, gravel, logs... and the front blade can level the soil.

It is fully mechanical and hydraulic, there is no electronic installed.

	DP-72-S	DP-82-S	DP-72-P	DP-82-P
<b>Kind of use</b>	Occasional	Occasional	Regular	Regular
<b>Weight in standard range</b>	550 kg	650 kg	570 kg	720 kg
<b>Engine</b>	6,5 HP Excalibur - 4,4 kW	9 HP Excalibur - 6,6 kW	9,5 HP Kohler - 7 kW	9,5 HP Kohler - 7kw
<b>Engine ignition</b>	Manual	Manual	Electric	Electric
<b>Track width</b>	720 mm	820 mm	720 mm	820 mm
<b>Tipping angle</b>	70°	70°	70°	70°
<b>Volume of the bucket</b>	200 L	320 L	200 L	320 L
<b>Payload</b>	300 kg	550 kg	400 kg	600 kg
<b>Traction motor</b>	Standard 200 cc	Standard 250 cc	Professional 200 cc	Professional 250 cc
<b>Distributors</b>	Non-proportional	Non-proportional	Proportional	Proportional
<b>Hydraulic pump flow</b>	Double - 13,3L/mn	Double - 23L/mn	Double - 23L/mn	Double - 23L/mn
<b>Included accessories</b>	Footboard	Footboard	Footboard, control levers protection plate, electrical ignition, blade	Footboard, control levers protection plate, electrical ignition, blade
<b>Prices</b>	<b>4300 € excl. taxes</b>	<b>4745 € excl. taxes</b>	<b>5190 € excl. taxes</b>	<b>5804 € excl. taxes</b>

## OPTIONS

- Control levers protection plate
- Electrical ignition
- Loading bucket
- Blade

# HANDLING AND PUBLIC WORKS DUMPSTER RAIL - CEMENT MIXER



The Dumpster is equipped with tilting and removable side panels and can move 600 kg and empty the contents owing to its hydraulic tipper.

The 270 L tipper can transport concrete, sand, soil.

It is fully mechanical and hydraulic, there is no electronic installed.

The Cement Mixer can move 130 L and empty the contents with a hydraulic tipping.

It is fully mechanical and hydraulic, there is no electronic installed.

	<b>BR-82-S</b>
<b>Weight in standard range</b>	720 kg
<b>Engine</b>	9 HP Excalibur - 6,6 kW
<b>Engine ignition</b>	Manual
<b>Track width</b>	820 mm
<b>Tipper dim. (L x W x H)</b>	890 mm, 700 mm, 350 mm
<b>Tipping angle</b>	70°
<b>Traction motor</b>	Standard 250 cc
<b>Distributors</b>	Non-proportional
<b>Hydraulic pump flow</b>	Double - 18L/mn
<b>Included accessories</b>	Footboard
<b>Prices</b>	<b>4985 € excl. taxes</b>

	<b>BT-72-S</b>
<b>Weight in standard range</b>	450 kg
<b>Engine</b>	6,5 HP Excalibur - 4,4 kW
<b>Engine ignition</b>	Manual
<b>Track width</b>	720 mm
<b>Mixer tank volume</b>	130 L
<b>Tipping angle</b>	60°
<b>Traction motor</b>	Standard 200 cc
<b>Distributors</b>	Non-proportional
<b>Hydraulic pump flow</b>	Double - 18L/mn
<b>Included accessories</b>	Footboard
<b>Prices</b>	<b>4990 € excl. taxes</b>

## OPTIONS

Electrical ignition

# AGRICULTURAL EQUIPMENT CRIQUET



The CRIQUET, with its main function of farm loader, can:

- move 150 kg or 200 kg and can lift a load up to 1,5 m or 2,00 m and empty the contents with its hydraulic tipper,
- move and maintain the load owing to the hydraulic claw installed on the bucket,
- to treat the moving of pallets or straw/hay bales owing to the adaptable pallet forks or bale spears,
- drill with the 100, 150 and 200 diameter of auger drilling attachments.

It is fully mechanical and hydraulic, there is no electronic installed.

	MC-72-S	MC-82-S	MC-72-P	MC-82-P
<b>Kind of use</b>	Occasional	Occasional	Regular	Regular
<b>Weight in standard range</b>	670 kg	780 kg	670 kg	780 kg
<b>Engine</b>	6,5 HP Excalibur - 4,4 kW	9 HP Excalibur - 6,6 kW	9,5 HP Kohler - 7 kW	9,5 HP Kohler - 7kw
<b>Engine ignition</b>	Manual	Manual	Electric	Electric
<b>Track width</b>	720 mm	820 mm	720 mm	820 mm
<b>Bucket volume</b>	100 L	100 L	100 L	100 L
<b>Lifting capacity</b>	150 kg	200 kg	150 kg	200 kg
<b>Lifting height</b>	1500 mm	2000 mm	1500 mm	2000 mm
<b>Traction motor</b>	Standard 200 cc	Standard 250 cc	Professional 200 cc	Professional 250 cc
<b>Hydraulic pump flow</b>	Double - 13,3L/mn	Double - 23L/mn	Double - 23L/mn	Double - 23L/mn
<b>Included accessories</b>	Footboard	Footboard	Footboard, control levers protection plate, electrical ignition, blade	Footboard, control levers protection plate, electrical ignition, blade
<b>Prices</b>	<b>6050 € excl. taxes</b>	<b>6949 € excl. taxes</b>	<b>7060 € excl. taxes</b>	<b>7868 € excl. taxes</b>

## OPTIONS

- Loading bucket included
- Hydraulic claw on bucket
- Electrical ignition
- Pallet forks (with support)
- Ball spears (with support)
- Specific complete auger drillings diam 100, 150 or 200 mm

# AGRICULTURAL EQUIPMENT FRONTAL LOADERS - RETRO EXCAVATORS



The Frontal loaders can:

- load, transport the earth with its 110 cm (standard) or 125 cm bucket,
- to maintain the load with the claw bucket,
- possible mounting of pallet forks or hay bale spikes owing to a specific support adaptation.

It is fully mechanical and hydraulic, there is no electronic installed.

This excavator is compatible with all tractors between 7 and 40 HP with a power take-off of 540 t/ min.

It is fully mechanical and hydraulic, there is no electronic installed.

	Frontal claw loader	Frontal ground loader
<b>Lifting capacity</b>	150 kg to 350 kg according to tractor weight	150 kg to 350 kg according to tractor weight
<b>Compatibility</b>	Tractors 7 to 25 HP	Tractors 7 to 25 HP
<b>Clearance</b>	Maximum 940 mm between left & right footboards (loader frame inside dimension)	Maximum 940 mm between left & right footboards (loader frame inside dimension)
<b>Hydraulic system</b>	Once the loader is fixed on the tractors, the hydraulic hoses can be connected to the tractor hydraulic connectors	Once the loader is fixed on the tractors, the hydraulic hoses can be connected to the tractor hydraulic connectors
<b>Prices</b>	<b>2548 € excl. taxes</b>	<b>1980 € excl. taxes</b>

	PR-1200-S	PR-1200-P	PR-1500-S	PR-1500-P
<b>Kind of use</b>	Occasional	Regular	Occasional	Regular
<b>Weight in standard range</b>	270 kg	270 kg	300 kg	300 kg
<b>Total width</b>	820 mm	820 mm	820 mm	820 mm
<b>Maximum height (arm lifted)</b>	1 900 mm	1 900 mm	2 000 mm	2 000 mm
<b>Maximum digging depth (from the ground)</b>	1 250 mm	1 250 mm	1 900 mm	1 900 mm
<b>Boom swing</b>	42° to right / 79° to left	42° to right / 79° to left	42° to right / 79° to left	42° to right / 79° to left
<b>Digging force</b>	1,2 T	1,2 T	1,5 T	1,5 T
<b>Hydraulic pump flow</b>	6cc gear pump - 10L/ mn	Double pump 6 + 6cc - 21L/ mn	6cc gear pump - 10L/ mn	Double pump 6 + 6cc - 21L/ mn
<b>Hydraulic stabilizers</b>	40 cm height adjustment	40 cm height adjustment	40 cm height adjustment	40 cm height adjustment
<b>Power of tractor</b>	Category 1 for 1,2 T	Category 1 for 1,2 T	Category 1 and 2 for 1,5 T	Category 1 and 2 for 1,5 T
<b>Included accessories</b>	Bucket 30 cm	Bucket 30 cm	Bucket 30 cm	Bucket 30 cm
<b>Prices</b>	<b>2990 € excl. taxes</b>	<b>3523 € excl. taxes</b>	<b>3585 € excl. taxes</b>	<b>4105 € excl. taxes</b>

## OPTIONS

Claw / Ground bucket 110 cm included  
 Claw bucket 125 cm (instead of 110 cm)  
 Ground bucket 125 cm (instead of 110 cm)  
 Pallet forks (with support)  
 Ball spears (with support)  
 Additionnal hydraulic line  
 Push Pull coupling  
 Push Pull bucket

Bucket quick coupler  
 Telescopic arm  
 Hydraulic hammer  
 Ripper 1 tooth  
 Ripper 4 teeth  
 Gripper fingers above the bucket  
 Bucket 20, 30, 60 cm (dredging)  
 Trapezium bucket, loading bucket  
 800 kgs grapple, 1,5 T grapple  
 Rigidity kit  
 Additionnal hydraulic line  
 Double pump  
 Push Pull bucket  
 Complete auger drilling 100, 150 or 200 mm  
 Log splitter



EQUIPMENT SOLUTIONS  
BY GO INDUSTRY



CHARGEUR PLUS  
3 rue Jacques de Vaucanson  
17180 Périgny  
FRANCE



contact@chargeurplus.fr  
+33 (0)5 46 56 18 88  
www.chargeurplus.com